

APC Smart-UPS X 1500VA Rack/Tower LCD 230V with Network Card

SMX1500RMI2UNC



- Includes: CD with software, Documentation CD, Installation guide, Rack mounting support rails, Removable support feet, Smart UPS signalling RS-232 cable, USB cable


Output

Output power capacity	1.2kWatts / 1.5kVA
Max Configurable Power (Watts)	1.2kWatts / 1.5kVA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 5 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Topology	Line interactive
Waveform type	Sine wave
Output Connections	(8) IEC 320 C13 (2) IEC Jumpers

Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz Auto-sensing
Input Connections	IEC 320 C14
Cord Length	1.8meters
Input voltage range for main operations	151 - 302 Adjustable, 160 - 286V
Number of Power Cords	1

Batteries & Runtime

Battery type	Lead-acid battery
Typical recharge time	3hour(s)
Replacement Battery	APCRBC115 

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Batteries & Runtime	
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	103 Watts
Extended Run Options	APC-Smart-UPS-X-1500VA-Rack-Tower-LCD-230V-with-Network-Card (Available in Technical Tab on site)
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	SmartSlot, USB
Pre-Installed SmartSlot™ Cards	AP9631 (Available in Technical Tab on site)
Control panel	Multifunction LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering	
Surge energy rating	645Joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical	
Maximum Height	89MM, 8.9CM
Maximum Width	432MM, 43.2CM
Maximum Depth	490MM, 49.0CM
Rack Height	2U
Net Weight	24.82KG
Shipping weight	30.0KG
Shipping Height	246MM, 24.6CM
Shipping Width	589MM, 58.9CM
Shipping Depth	620MM, 62.0CM
Color	Black

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Units per Pallet	8.0

Environmental	
Operating Temperature	0 - 45 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	40.0dBA
Online thermal dissipation	133.0BTU/hr

Conformance	
Approvals	C-Tick, CE, EAC, EN 50091-1, EN 50091-2, VDE
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

Sustainable Offer Status	
RoHS	Compliant
PEP	Available in Documentation tab
EOLI	Available in Documentation tab

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.