

DYNAMIX DOME ENCLOSURE

DESCRIPTION

The Dynamix Compact Dome Closure offers an innovative solution for managing up to 60 fibers, featuring a hinged door for easy access and maintenance. Built to withstand harsh environments with an IP68 rating, this ruggedized enclosure supports various FTTH installation methods, including wall-mounted and aerial setups. With multiple cable entry sizes, it provides exceptional flexibility to accommodate different cable installations

FEATURES

- Compact with integrated fiber management
- Outdoor IP68 Rated
- Easy operation with hinged door
- Mechanical sealing with multiple cable entry points



PRODUCT CODE

OC-DO06-24

DESCRIPTION

DYNAMIX OUTDOOR IP68 FIBRE DOME ENCLOSURE

COLOUR

Black

SPECIFICATIONS

Dimensions (HxWxD)	300 x 220 x 100 mm	Suitable Fiber Cable OD	Φ8mm - Φ15mm
Weight (Kg)	2.4 - 2.7 Kg	Number of Φ2mm Entries	4
Material	ABS	Sealing Structure	Mechanical Compression
Splice Tray Capacity	12 Fibres	Sealing Rating	IP68
Max Number of Trays	5pcs	Operating Temperature	-40°C ~ 65°C
Max. Capacity (Fibers)	60 Fibres	Impact Strength	10 N.m/IK08

Please note we took the up-most care to compile the information in this datasheet. To the best of our knowledge all info provided were correct at the time of creation. Should any specs change we try to update info accordingly. Information are subject to change without notice. In the case that you find any irregularity please inform our team at contactus@dynamix.co.nz

Last updated: 07112024