Eaton EVBAF116A

FITT

Catalog Number: EVBAF116A

Eaton Basic G4 Rack PDU, 0U, 22.5U, IEC-60309 input, 3m cord, 1ph, 3.7kW, 16A, 200-240V, 24 outlets (12)C13, (12)C39

General specifications

Product Name Eaton Rack PDU G4

EAN 3553340697296

Product Height 53 mm

Product Weight 2.15 kg

Compliances

CB LVD Directive RoHS Directive WEEE Directive Packaging Directive

Model Code

PDU G4 BA 0U 309 16A 1P 12xC13,12xC39 Catalog Number EVBAF116A

Product Length/Depth 1000 mm

Product Width 52 mm

Warranty

3 year

Certifications

IEC 62368-1 EN IEC 63000 CE EAC UKCA Cm Ukr



Electrical input

Input connection IEC-60309 16A 1Ph

Wattage

3.7 kW max

Amperage Rating

16A

Input voltage 200-240V

Phase

Single-phase

Frequency rating

50/60 Hz

Cord length

3m

Electrical output

Outlets

(12) C13, (12) C39
Number of Outputs C13
12
Number of Outputs C19
12
Number of outputs (other)
12
Number of outlets with earth pin
24

Technology & communications

Type Basic Rack PDU

Outlet control

No

Special features

Versatile C39 outlet supports C14 or C20 power cord plug High retention outlets designed to securely fit standard power cords and support P-Lock power cords Color-coded outlet banks and corresponding circuit breakers

Ethernet interface

No

Serial interface

No

SNMP

No

Communication

No

Mass configuration

Additional specifications

Operating Temperature

0° to 60°C (32° to 140°F)

Accessories

Rack PDU Rack mounting accessories Quickstart guide Safety Instructions

Material

Aluminium

Color

Black

Resources

Brochures Rack PDU G4 Brochure EN

Declarations of conformity EU declaration of conformity Rack PDU G4



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia