

Eaton EVBAF132A

Catalog Number: EVBAF132A

Eaton Basic G4 Rack PDU, 0U, 22.5U, IEC-60309 input, 3m cord, 1ph, 7.4kW, 32A, 200-240V, 24 outlets (12)C13, (12)C39

General specifications



Product Name	Catalog Number
Eaton Rack PDU G4	EVBAF132A
EAN	Product Length/Depth
3553340697197	1000 mm
Product Height	Product Width
53 mm	52 mm
Product Weight	Warranty
2.4 kg	3 year
Compliances	Certifications
CB	IEC 62368-1
LVD Directive	EN IEC 63000
RoHS Directive	CE
WEEE Directive	EAC
Packaging Directive	UKCA
	Cm
	Ukr
Model Code	
PDU G4 BA 0U 309 32A 1P 12xC13,12xC39	

Electrical input

Input connection

IEC-60309 32A 1Ph

Wattage

7.4 kW max

Amperage Rating

32 A

Input voltage

200-240V

Phase

Single-phase

Circuit breaker

(2) single-pole

Frequency rating

50/60 Hz

Cord length

3m

Electrical output

Outlets

(12) C13, (12) C39

Number of Outputs C13

12

Number of Outputs C19

12

Number of outputs (other)

12

Number of outlets with earth pin

24

Technology & communications

Type

Basic Rack PDU

Outlet control

No

Special features

Versatile C39 outlet
supports C14 or C20 power
cord plug
High retention outlets
designed to securely fit
standard power cords and
support P-Lock power cords
Color-coded outlet banks
and corresponding circuit
breakers

Ethernet interface

No

Serial interface

No

SNMP

No

Communication

No

Mass configuration

No

Additional specifications

Operating Temperature

0° to 60°C (32° to 140°F)

Accessories

Rack PDU
Rack mounting accessories
Quickstart guide
Safety Instructions

Material

Aluminium

Color

Black

Resources

Brochures

[Rack PDU G4 Brochure EN](#)

Declarations of conformity

[EU declaration of conformity Rack PDU G4](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)