

### PRODUCT SPECIFICATION

#### DESCRIPTION

This lockable IP65 distribution box offers the ability to terminate 12 fibres housed in a strong robust ABS enclosure for indoor and outdoor applications. An internal detachable tray provides a neat and tidy solution for housing 12 SC simplex connections and splices. The box has 12 patch cord exit points and up to 2 cable entry points which maintain the IP65 rating. Integrated cable tie points are included to secure incoming cables. A locking feature for the door adds extra security when positioned in an unsecured area.



#### FEATURES

- IP 65 Rating for external use
- Lockable door for added security
- Integrated cable tie points for securing incoming cable
- Up to 12 splice & SC connection points
- Removable splice tray for easy installation
- Accepts loose tube, distribution and pre-terminated cables
- Integrated bend radius protection
- Sealing glands for up to 12 exiting cables + 2 x 6.5mm- 13mm incoming cable
- Removable door for ease of installation
- Supplied with 12 heatshrink splice protectors
- Supplied with transit tubing
- Supplied with wall fixings and tie wraps

#### SPECIFICATIONS

Height (mm)	235
Width (mm)	205
Depth (mm)	60
Net weight (kg)	0.9
Suitable for adaptor type	SC Simplex
Number of ports	12
Cable entry	2
Material	ABS
Colour	Grey RAL 7035
Operating temperature (°C)	-40 to +60
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754, EN297-1
Compliant to	RoHS, Reach/SVHC