# PAAG-E3122 (2 Port) PAAG-E3124A (4 Port)



# 4K@60Hz Dual-View DisplayPort KVM Switch

with USB 3.2 Gen1 & Hotkey Control

# **▶** Specifications

Model		PAAG-E3122	PAAG-E3124A
Console Port		1	
Computer Port		2	4
Front Panel Push Button		1	4
Resolution (Max.)		3840 x 2160 @ 60Hz (4:4:4) 4096 x 2160 @ 60Hz (4:4:4)	
Computer ready LED, (Green)		2	4
Computer selected LED, (Red)		2	4
Computer Interface	USB 3.2 Gen 1	USB-B x 2	USB-B x 4
	Video Input	DP x 4 (Dual-View x 2)	DP x 8 (Dual-View x 4)
	Audio Jack In	2	4
Console Interface	USB 3.2 Gen 1	USB-A x 2 (Front x 1,Rear x 1)	
	USB HID Port	USB-A x 4 (Front x 3,Rear x 1) ( KB/MS/Touch Screen )	
	Video Output	DisplayPort x 2 (Dual-View)	
	Audio Jack Out	1 (Speaker)	
Keyboard Hotkey		Yes	
Auto Scan Interval		3, 8, 15, 30, seconds	
Cable Length (Max)		3M (10ft) for USB	
Hot Plug-n-Play		Yes	
Power Supply		DC 9-12V	
H x W x D (mm)		60 x 160 x 100	60 x 220 x 130

#### **▶** Features

- Allow 2/4 Dual-View Computers to Share USB Console & Peripherals ( 4 x HID device + 2 x USB 3.2 Gen1 )
- 4K @ 60Hz (4:4:4) Max. Resolution Support
- Support Keyboard and Mouse Plug-n-Play without Drivers
- Front Panel Buttons & Hotkey Controls for Easy Computer Selection
- Auto Scan Support & Selectable Scan Time Interval
- Windows and Mac Supported and No Software Required

## ► Highlight Features

- Front USB 3.2 Gen1 Port Design for Easy Apply of USB Devices
- USB 3.2 Gen1 Provides Excellent Speed

#### PAAG-E3122



#### PAAG-E3124A



### ► Connection pattern







Dual-View USB Console + Audio

## Also Avialable:

VGA / DVI / HDMI KVM Model with Different ports number and usb 2.0/ 3.0 for selection

Dual-View Computers x 4