

TCT-490 Tone Tracing Kit

Date	Rev.	Description

Tone Probe	
Tone Signals Detect (200M UTP) base on (TCT-470 Toner)	108 dB
Power Switch for Test	ON/OFF Push Button
Adjustable Volume Control	Rotary Switch
Replaceable Tip	Plastic Tip(300Ω) Only
LED Signal Indicator	Φ=5mm Red LED
LED Battery Low Indicator	Yes
Test Telephone Port	Yes
Headset Jack	3.5 mm stereo plug; 8 ohms minimum
Battery	alkaline Battery (+9V DC)
Operating/Storage Temperature	(-20 ~ +60 ℃); (-40 ~ +70 ℃)
Tone Generator	
Output Power	Talk Battery(into 600Ω): 12 VDC Output Power(into 600Ω): +10dBa
Continuity & Polarity LED	Yes
External Warble Select	External Warble Select by (Panel Key PAD) Frequency: (Alternating 890/960Hz)
Signals Output Ports (RJ11)	RJ11 Plug with Cable.
Short Circuit LED/Beeper	Only Short Circuit LED. Resistive Short Visual Indication: <10 KΩ
Alligator/ABN Connector Clips	Alligator
Over Voltage Protection	24 Vdc in Toner/Polarity Mode
Battery	alkaline Battery (+9V DC)
Operating Temperature	(-20 ~ +60 ℃)
Storage Temperature	(-40 ~ +70 ℃)



DCC. NO.
A4 DRAWING NO.

MATERIAL:	GOLDSUN ELECTRONICS CO., LTD.			
	GOLDSUN NO.		TCT-490	
DRAWN: nomo	Description			Rev. 1
VERIFY PEOPLE: Chesley	UNIT: mm	SCALE:	SHEET 1 OF 1	CAS No: ERN No:

TCT-490 Tone Tracing Kit

Date	Rev.	Description

Tone Probe	
Tone Signals Detect (200M UTP) base on (TCT-470 Toner)	108 dB
Power Switch for Test	ON/OFF Push Button
Adjustable Volume Control	Rotary Switch
Replaceable Tip	Plastic Tip(300Ω) Only
LED Signal Indicator	Φ=5mm Red LED
LED Battery Low Indicator	Yes
Test Telephone Port	Yes
Headset Jack	3.5 mm stereo plug; 8 ohms minimum
Battery	alkaline Battery (+9V DC)
Operating/Storage Temperature	(-20 ~ +60 ℃); (-40 ~ +70 ℃)
Tone Generator	
Output Power	Talk Battery(into 600Ω): 12 VDC Output Power(into 600Ω): +10dBm
Continuity & Polarity LED	Yes
External Warble Select	External Warble Select by (Panel Key PAD) Frequency: (Alternating 890/960Hz)
Signals Output Ports (RJ11)	RJ11 Plug with Cable.
Short Circuit LED/Beeper	Only Short Circuit LED. Resistive Short Visual Indication: <10 KΩ
Alligator/ABN Connector Clips	Alligator
Over Voltage Protection	24 Vdc in Toner/Polarity Mode
Battery	alkaline Battery (+9V DC)
Operating Temperature	(-20 ~ +60 ℃)
Storage Temperature	(-40 ~ +70 ℃)



DCC. NO.
A4 DRAWING NO.

MATERIAL:	GOLDSUN ELECTRONICS CO., LTD.			
	GOLDSUN NO.			TCT-490
DRAWN: nomo	Description		Rev. 1	
VERIFY PEOPLE: Chesley	UNIT: mm	SCALE:	SHEET 1 OF 1	CAS No: ERN No: