# 

### SAFEGUARD 1000VA/600W LINE INTERACTIVE UPS

#### DESCRIPTION

The DYNAMIX SafeGuard 1000VA UPS provides a buffer between your equipment and inconsistent mains power supply. This cost effective, compact device constantly stands guard beside your sensitive equipment. The informative display and USB charging port are unique to this model and offer a complete solution for protecting valuable equipment.

#### **FEATURES**

- Automatic Voltage Regulation (Buck and Boost)
- Informative Screen Display
- USB Charging Port
- Light-weight compact and elegantly designed
- Intelligent microprocessor control
- Monitoring and shutdown software included
- Overload protection and alarm
- Output short circuit protection
- Start on battery function (cold start)
- USB communication
- Easy user-replaceable battery
- Australian/New Zealand approved sockets
- Wall mountable
- 2 Year warranty







#### **SPECIFICATIONS**

Capacity	1000VA / 600W Line interactive	
INPUT		
Voltage	240Vac (Nominal)	
Voltage range	177~290Vac	
Frequency	50Hz or 60Hz (Auto sensing	
OUTPUT		
Output Voltage	240Vac ±10%	
Frequency range (Batt. Mode)	50Hz or 60Hz ±-1Hz	
Transfer time	6 msec (Typical)	
Wave Form (Batt. Mode)	Simulated Sine Wave	
NZ Outlets	4 (UPS and Surge Protection)	
NZ Outlets	4 (Full Time Surge Protection)	
BATTERY		
Capacity	12Vx9AH	
Backup Time	25min (1 PC load at 100W)	
Typical Recharge Time	6~8 hours recover to 90% capacity	
PROTECTION		
Full protection	Overcharge, discharge, short circuit and thermal protection	
Surge protection	475Joules /13000Amps - Best in its class	

## 

### **SPECIFICATIONS**

COMMUNICATIONS & MANAGEMENT		
Interface	USB interface	
Software	PowerShield® NetGuard® supports Windows, Linux, Unix & Mac	
LED Alarm	AC Mode, Battery Mode, Low Battery (Batt. Mode), Fault	
Audible Alarm	Battery Mode, Low Battery (Batt. Mode), Fault	
PHYSICAL		
Dimensions L x W x H	345 x 200 x 100mm	
Weight	6.1kg	
OPERATING ENVIRONMENTS		
Temperature	0°C~40°C	
Humidity	0%-90% (RH Non-condensing)	
Noise level	<5dB (No Fan)	
COMPLIANCE		
Safety	Safety EN62040 - 1 - 1 2003, IEC60950 - 1: 2001	
EMC	EN62040 - 2 2006	
RoHS	Directive 2011/65/EU	



#### UPSG750 **UPSE1000 UPSD1200 UPSD2000** Defender Defender ECO Range 1200VA/720W 2000VA/1200W (II-B 01 240 00240 1000VA/600W Line Interactive Line Interactive UPS, 3x NZ Power UPS, 3x NZ Line Interactive å 750VA/450W Line Interactive UPS, UPS. 3x NZ Sockets with Power Sockets 4 3x NZ Battery Back Up & Surge Power Sockets. Surge + Battery with Surge + Backup Outlets, 3x NZ Surge Only Outlets Battery Backup. Battery Backup

Please note we took the up-most care to compile the information in this datasheet. To the best of our knowledge all info provided were correct at the time of creation. Should any specs change we try to update info accordingly. Information are subject to change without notice. In the case that you find any irregularity please inform our team at **contactus@dynamix.co.nz** Last updated: 14 September 2021

**ALSO AVAILABLE:**